


Specifications

Fiber Optic Keystone Modules

KEY FEATURES

- Meets ANSI/TIA-568-C.3 transmission performance specifications
- Universal keystone design with configurable patch panels for the enterprise or data center
- Precise measurements for ferrule alignment to reduce insertion loss
- Multi-purpose flexibility - fitting with the SIGNAMAX Just Right Density™ product offering collection



ORDERING INFORMATION

PART NO.	DESCRIPTION
SC CONNECTIONS	
CMK-SCG	SC OM3/OM4 Keystone Connector Module, Light Ivory
CMK-SCS	SC SM Keystone Connector Module, Light Ivory
LC CONNECTIONS	
CMK-LCG	LC OM3/OM4 Keystone Connector Module, Light Ivory
CMK-LCS	LC SM Keystone Connector Module, Light Ivory
BLANK	
CMK-BL	Blank Keystone Module (package of ten), Light Ivory

For other colors add the following to P/N:



Additional module colors and legacy connectors (OM1) available by request, contact customer service.

SPECIFICATIONS

TRANSMISSION PERFORMANCE

ANSI/TIA-568-C.3: exceeds component specifications

TRANSMISSION MEDIA

Multimode: OM1, OM3, OM4

Singlemode: UPC, APC

Insertion Loss: 0.20 dB Typical, 0.40 dB Max

Insertion loss increase after 500 mating cycles: 0.10 dB

DIMENSIONS

SC: 1.10" D x 0.67" W x 0.76" H (28 mm x 16.9 mm x 19.3 mm) LC:

1.00" D x 0.67" W x 0.76" H (28 mm x 16.9 mm x 19.3 mm)

CONSTRUCTION

Housing: High impact thermoplastic, UL94V-0 fire retardant

Sleeve: Zirconia ceramic

MECHANICAL

Sleeve/Ferrule Withdraw Force:

1.96 N (200 gf) (0.44 lbf) – 5.88 N (600 gf) (1.32 lbf)

Mating cycle life: Min 500 cycles

ENVIRONMENTAL CONDITIONS

Operating & Storage Temperature: -40 to 185°F (-40 to 85°C)

Operating RH: 93% (non-condensing)

COMPLIANCE

ANSI/TIA-568-C.3, FOCIS, UL94V-0

WARRANTY

5 - Year Limited Component

